

Chapter f06 – Linear Algebra Support Functions

1. Scope of the Chapter

This Chapter is concerned with basic linear algebra functions which perform elementary algebraic operations involving vectors and matrices.

2. Background

All the functions in this chapter meet the specification of the Basic Linear Algebra Subprograms (BLAS) in C as described in Datardina et al (1992). These in turn were derived from the pioneering work of Dongarra *et al* (1988) and Dongarra *et al* (1990) on Fortran 77 BLAS. The functions described are concerned with matrix-vector operations and matrix-matrix operations. These will be referred to here as the Level-2 BLAS and Level-3 BLAS respectively. The terminology reflects the number of operations involved. For example, a Level-2 function involves $O(n^2)$ operations for an n by n matrix. The Level 1 Blas will be included at a future mark of the C Library.

Table 1.1 indicates the NAG coded naming scheme for the functions in this Chapter.

		Level-2	Level-3
'real'	BLAS function	f06p_c	f06y_c
'complex'	BLAS function	f06s_c	f06z_c

The C BLAS names for these functions are the same as the corresponding Fortran names except that they are in lower case.

The functions in this chapter do not have full function documents, but instead are covered by general descriptions in Section 4 sufficient to enable their use. As this chapter is concerned only with basic linear algebra operations, the functions will not normally be required by the general user. The purpose of each function is indicated in Section 3 so that those users requiring these functions to build specialist linear algebra modules can determine which functions are of interest.

3. References

- Datardina S P, Du Croz J J, Hammarling S J and Pont M W (1992) A Proposed Specification of BLAS Routines in C *The Journal of C Language Translation* **3** 295–309.
- Dongarra J J, Du Croz J J, Hammarling S and Hanson R J (1988) An Extended Set of FORTRAN Basic Linear Algebra Subprograms *ACM Trans. Math. Softw.* **14** 1–32.
- Dongarra J J, Du Croz J J, Duff I S and Hammarling S (1990) A Set of Level 3 Basic Linear Algebra Subprograms *ACM Trans. Math. Softw.* **16** 1–28.

4. Recommendations on Choice and Use of Functions

This section lists the functions in the categories Level-2 (matrix-vector) and Level-3 (matrix-matrix). The corresponding BLAS name is indicated in brackets.

Within each section functions are listed in alphabetic order of the fifth character in the short function name, so that corresponding real and complex functions may have adjacent entries.

4.1. The Level-2 Matrix-vector Functions

The Level-2 functions perform matrix-vector operations, such as forming the product between a matrix and a vector.

Compute a matrix-vector product; real general matrix	dgemv (f06pac)
Compute a matrix-vector product; complex general matrix	zgemv (f06sac)
Compute a matrix-vector product; real general band matrix	dgbmv (f06pbc)
Compute a matrix-vector product; complex general band matrix	zgbmv (f06sbc)
Compute a matrix-vector product; real symmetric matrix	dsymv (f06ppc)
Compute a matrix-vector product; complex Hermitian matrix	zhemv (f06scc)
Compute a matrix-vector product; real symmetric band matrix	dsbmv (f06pdc)
Compute a matrix-vector product; complex Hermitian band matrix	zhbm (f06sdc)
Compute a matrix-vector product; real symmetric packed matrix	dspmv (f06pec)
Compute a matrix-vector product; complex Hermitian packed matrix	zhpmv (f06sec)
Compute a matrix-vector product; real triangular matrix	dtrmv (f06pfc)
Compute a matrix-vector product; complex triangular matrix	ztrmv (f06sfc)
Compute a matrix-vector product; real triangular band matrix	dtbmv (f06pgc)
Compute a matrix-vector product; complex triangular band matrix	ztbmv (f06sgc)
Compute a matrix-vector product; real triangular packed matrix	dtpmv (f06phc)
Compute a matrix-vector product; complex triangular packed matrix	ztpmv (f06shc)
Solve a system of equations; real triangular coefficient matrix	dtrsv (f06pjc)
Solve a system of equations; complex triangular coefficient matrix	ztrsv (f06sjc)
Solve a system of equations; real triangular band coefficient matrix	dtbsv (f06pkc)
Solve a system of equations; complex triangular band coefficient matrix	ztbsv (f06skc)
Solve a system of equations; real triangular packed coefficient matrix	dtpsv (f06plc)
Solve a system of equations; complex triangular packed coefficient matrix	ztpsv (f06slc)
Perform a rank-one update; real general matrix	dger (f06pmc)
Perform a rank-one update; complex general matrix (unconjugated vector)	zgeru (f06smc)
Perform a rank-one update; complex general matrix (conjugated vector)	zgerc (f06snc)
Perform a rank-one update; real symmetric matrix	dsyr (f06ppc)
Perform a rank-one update; complex Hermitian matrix	zher (f06spc)
Perform a rank-one update; real symmetric packed matrix	dspr (f06ppc)
Perform a rank-one update; complex Hermitian packed matrix	zhpr (f06sqc)
Perform a rank-two update; real symmetric matrix	dsyr2 (f06prc)
Perform a rank-two update; complex Hermitian matrix	zher2 (f06src)
Perform a rank-two update; real symmetric packed matrix	dspr2 (f06psc)
Perform a rank-two update; complex Hermitian packed matrix	zhpr2 (f06ssc)

4.2. The Level-3 Matrix-matrix Functions

The Level-3 functions perform matrix-matrix operations, such as forming the product of two matrices.

Compute a matrix-matrix product; two real rectangular matrices	dgemm (f06yac)
Compute a matrix-matrix product; two complex rectangular matrices	zgemm (f06zac)
Compute a matrix-matrix product; one real symmetric matrix, one real rectangular matrix	dsymm (f06ycc)

Compute a matrix-matrix product; one complex Hermitian matrix, one complex rectangular matrix	<code>zhemm (f06zcc)</code>
Compute a matrix-matrix product; one real triangular matrix, one real rectangular matrix	<code>dtrmm (f06yfc)</code>
Compute a matrix-matrix product; one complex triangular matrix, one complex rectangular matrix	<code>ztrmm (f06zfc)</code>
Solve a system of equations with multiple right-hand sides, real triangular coefficient matrix	<code>dtrsm (f06yjc)</code>
Solve a system of equations with multiple right-hand sides, complex triangular coefficient matrix	<code>ztrsm (f06zjc)</code>
Perform a rank- k update of a real symmetric matrix	<code>dsyrk (f06ypc)</code>
Perform a rank- k update of a complex hermitian matrix	<code>zherk (f06zpc)</code>
Perform a rank- $2k$ update of a real symmetric matrix	<code>dsyr2k (f06yrc)</code>
Perform a rank- $2k$ update of a complex Hermitian matrix	<code>zher2k (f06zrc)</code>
Compute a matrix-matrix product: one complex symmetric matrix, one complex rectangular matrix	<code>zsymm (f06ztc)</code>
Perform a rank- k update of a complex symmetric matrix	<code>zsyrk (f06zuc)</code>
Perform a rank- $2k$ update of a complex symmetric matrix	<code>zsyr2k (f06zwc)</code>

5. Description of the f06 Functions

The argument lists use the following data types.

Integer: an integer data type of at least 32 bits.

double: the regular double precision floating-point type.

Complex: a double precision complex type.

plus the enumeration types given by

```
typedef enum { NoTranspose, Transpose, ConjugateTranspose } MatrixTranspose;
typedef enum { UpperTriangle, LowerTriangle } MatrixTriangle;
typedef enum { UnitTriangular, NotUnitTriangular } MatrixUnitTriangular;
typedef enum { LeftSide, RightSide } OperationSide;
```

In this section we describe the purpose of each function and give information on the argument lists, where appropriate indicating their general nature. Usually the association between the function arguments and the mathematical variables is obvious and in such cases a description of the argument is omitted.

Within each section, the argument lists for all functions are presented, followed by the purpose of the functions and information on the argument lists.

Within each section functions are listed in alphabetic order of the fifth character in the function name, so that corresponding real and complex functions may have adjacent entries.

5.1. The Level-2 Matrix-vector Functions

The matrix-vector functions all have one array argument representing a matrix; usually this is a two-dimensional array but in some cases the matrix is represented by a one-dimensional array.

The size of the matrix is determined by the arguments **m** and **n** for an m by n rectangular matrix; and by the argument **n** for an n by n symmetric, Hermitian, or triangular matrix. Note that it is permissible to call the functions with **m** or **n** = 0, in which case the functions exit immediately without referencing their array arguments. For band matrices, the bandwidth is determined by the arguments **kl** and **ku** for a rectangular matrix with **kl** sub-diagonals and **ku** super-diagonals; and by the argument **k** for a symmetric, Hermitian, or triangular matrix with **k** sub-diagonals and/or super-diagonals.

The description of the $m \times n$ matrix consists either of the array name (**a**) followed by the trailing (last) dimension of the array as declared in the calling (sub)program (**tda**), when the matrix is being stored in a two-dimensional array; or the array name (**ap**) alone when the matrix is being stored as a (packed) vector. In the former case the actual array must be allocated at least $((m-1)d+l)$ contiguous elements, where d is the trailing dimension of the array, $d \geq l$, and $l = n$ for arrays representing general, symmetric, Hermitian and triangular matrices, $l = kl + ku + 1$ for arrays representing general band matrices and $l = k + 1$ for symmetric, Hermitian and triangular band matrices. For one-dimensional arrays representing matrices (**packed storage**) the actual array must contain at least $\frac{1}{2}n(n+1)$ elements.

The length of each vector, n , is represented by the argument **n**, and the routines may be called with non-positive values of **n**, in which case the routine returns immediately.

In addition to the argument **n**, each vector argument also has an **increment** argument that immediately follows the vector argument, and whose name consists of the three characters **inc**, followed by the name of the vector. For example, a vector x will be represented by the two arguments **x**, **incx**. The increment argument is the spacing (stride) in the array for which the elements of the vector occur. For instance, if **incx** = 2, then the elements of x are in locations **x**[0], **x**[2], ..., **x**[2 * **n** - 2] of the array **x** and the intermediate locations **x**[1], **x**[3], ..., **x**[2 * **n** - 3] are not referenced.

Zero increments are not permitted. When **incx** > 0, the vector element x_i is in the array element **x**[($i-1$) * **incx**], and when **incx** < 0 the elements are stored in the reverse order so that the vector element x_i is in the array element **x**[-($n-i$) * **incx**] and hence, in particular, the element x_n is in **x**[0]. The declared length of the array **x** in the calling (sub)program must be at least $(1 + (n-1) * |\mathbf{incx}|)$.

The arguments that specify options are enumeration arguments with the names **trans**, **uplo** and **diag**. **trans** is used by the matrix-vector product functions as follows:

Value	Meaning
NoTranspose	Operate with the matrix
Transpose	Operate with the transpose of the matrix
ConjugateTranspose	Operate with the conjugate transpose of the matrix

In the real case the values **Transpose** and **ConjugateTranspose** have the same meaning.

uplo is used by the Hermitian, symmetric, and triangular matrix functions to specify whether the upper or lower triangle is being referenced as follows:

Value	Meaning
UpperTriangle	Upper triangle
LowerTriangle	Lower triangle

diag is used by the triangular matrix functions to specify whether or not the matrix is unit triangular, as follows:

Value	Meaning
UnitTriangular	Unit triangular
NotUnitTriangular	Non-unit triangular

When **diag** is supplied as **UnitTriangular**, the diagonal elements are not referenced.

5.1.1. Matrix storage schemes

Conventional storage

The default scheme for storing matrices is the obvious one: a matrix A is stored in a 2-dimensional array **A**, with matrix element a_{ij} stored in array element **A**(i, j).

If a matrix is **triangular** (upper or lower, as specified by the argument **uplo**), only the elements of the relevant triangle are stored; the remaining elements of the array need not be set. Such elements are indicated by * in the examples below. For example, when $n = 4$:

uplo	Triangular matrix A	Storage in array A
UpperTriangle	$\begin{pmatrix} a_{11} & a_{12} & a_{13} & a_{14} \\ & a_{22} & a_{23} & a_{24} \\ & & a_{33} & a_{34} \\ & & & a_{44} \end{pmatrix}$	$\begin{matrix} a_{11} & a_{12} & a_{13} & a_{14} \\ * & a_{22} & a_{23} & a_{24} \\ * & * & a_{33} & a_{34} \\ * & * & * & a_{44} \end{matrix}$
LowerTriangle	$\begin{pmatrix} a_{11} & & & \\ a_{21} & a_{22} & & \\ a_{31} & a_{32} & a_{33} & \\ a_{41} & a_{42} & a_{43} & a_{44} \end{pmatrix}$	$\begin{matrix} a_{11} & * & * & * \\ a_{21} & a_{22} & * & * \\ a_{31} & a_{32} & a_{33} & * \\ a_{41} & a_{42} & a_{43} & a_{44} \end{matrix}$

Routines which handle **symmetric** or **Hermitian** matrices allow for either the upper or lower triangle of the matrix (as specified by **uplo**) to be stored in the corresponding elements of the array; the remaining elements of the array need not be set. For example, when $n = 4$:

uplo	Hermitian matrix A	Storage in array A
UpperTriangle	$\begin{pmatrix} a_{11} & a_{12} & a_{13} & a_{14} \\ \bar{a}_{12} & a_{22} & a_{23} & a_{24} \\ \bar{a}_{13} & \bar{a}_{23} & a_{33} & a_{34} \\ \bar{a}_{14} & \bar{a}_{24} & \bar{a}_{34} & a_{44} \end{pmatrix}$	$\begin{matrix} a_{11} & a_{12} & a_{13} & a_{14} \\ * & a_{22} & a_{23} & a_{24} \\ * & * & a_{33} & a_{34} \\ * & * & * & a_{44} \end{matrix}$
LowerTriangle	$\begin{pmatrix} a_{11} & \bar{a}_{21} & \bar{a}_{31} & \bar{a}_{41} \\ a_{21} & a_{22} & \bar{a}_{32} & \bar{a}_{42} \\ a_{31} & a_{32} & a_{33} & \bar{a}_{43} \\ a_{41} & a_{42} & a_{43} & a_{44} \end{pmatrix}$	$\begin{matrix} a_{11} & * & * & * \\ a_{21} & a_{22} & * & * \\ a_{31} & a_{32} & a_{33} & * \\ a_{41} & a_{42} & a_{43} & a_{44} \end{matrix}$

Packed storage

Symmetric, Hermitian or triangular matrices may be stored more compactly, if the relevant triangle (again as specified by **uplo**) is packed by rows in a 1-dimensional array.

- if **uplo** = **UpperTriangle**, a_{ij} is stored in **ap** $[j - 1 + (2n - i)(i - 1)/2]$ for $i \leq j$;
- if **uplo** = **LowerTriangle**, a_{ij} is stored in **ap** $[j - 1 + i(i - 1)/2]$ for $j \leq i$.

For example:

uplo	Triangular matrix a	Packed storage in array ap
UpperTriangle	$\begin{pmatrix} a_{11} & a_{12} & a_{13} & a_{14} \\ & a_{22} & a_{23} & a_{24} \\ & & a_{33} & a_{34} \\ & & & a_{44} \end{pmatrix}$	$\underbrace{a_{11} \ a_{12} \ a_{13} \ a_{14}}_{\text{row 1}} \underbrace{a_{22} \ a_{23} \ a_{24}}_{\text{row 2}} \underbrace{a_{33} \ a_{34}}_{\text{row 3}} \underbrace{a_{44}}_{\text{row 4}}$
LowerTriangle	$\begin{pmatrix} a_{11} & & & \\ a_{21} & a_{22} & & \\ a_{31} & a_{32} & a_{33} & \\ a_{41} & a_{42} & a_{43} & a_{44} \end{pmatrix}$	$\underbrace{a_{11}}_{\text{row 1}} \underbrace{a_{21} \ a_{22}}_{\text{row 2}} \underbrace{a_{31} \ a_{32} \ a_{33}}_{\text{row 3}} \underbrace{a_{41} \ a_{42} \ a_{43} \ a_{44}}_{\text{row 4}}$

Note that for real symmetric matrices, packing the upper triangle by rows is equivalent to packing the lower triangle by columns; packing the lower triangle by rows is equivalent to packing the upper triangle by columns. (For complex Hermitian matrices, the only difference is that the off-diagonal elements are conjugated.)

Band storage

A band matrix with kl subdiagonals and ku superdiagonals may be stored compactly in a 2-dimensional array with $kl + ku + 1$ columns and m rows. Rows of the matrix are stored in corresponding rows of the array, and diagonals of the matrix are stored in columns of the array.

For example, when $n = 5$, $kl = 2$ and $ku = 1$:

Band Matrix a	Band storage in array ab			
$\begin{pmatrix} a_{11} & a_{12} & & & \\ a_{21} & a_{22} & a_{23} & & \\ a_{31} & a_{32} & a_{33} & a_{34} & \\ & a_{42} & a_{43} & a_{44} & a_{45} \\ & & a_{53} & a_{54} & a_{55} \end{pmatrix}$	*	*	a_{11}	a_{12}
	*	a_{21}	a_{22}	a_{23}
	a_{31}	a_{32}	a_{33}	a_{34}
	a_{42}	a_{43}	a_{44}	a_{45}
	a_{53}	a_{54}	a_{55}	*

The elements marked * in the upper left $k_l \times k_l$ triangle and lower right $k_u \times k_u$ of the array **ab** need not be set, and are not referenced by the routines.

The following code fragment will transfer a band matrix $A(m, n)$ from conventional storage to band storage **ab**

```
for(i=0; i<m; ++i){
    k+kl-i;
    for (j=MAX(0,i-kl); j<=MIN(n-1,i+ku); ++j){
        ab[i][k+j]=A[i][j];
    }
}
```

Triangular band matrices are stored in the same format, with either $kl = 0$ if upper triangular, or $ku = 0$ if lower triangular.

For symmetric or Hermitian band matrices with k subdiagonals or superdiagonals, only the upper or lower triangle (as specified by **uplo**) need be stored:

The following code fragments will transfer a symmetric or Hermitian matrix $A(n, n)$ from conventional storage to band storage **ab**

if **uplo**=UpperTriangle

```
for(i=0; i<n; ++i){
    l=-i;
    for (j=i; j<=MIN(n-1,i+k); ++j){
        ab[i][l+j]=A[i][j];
    }
}
```

if **uplo**=LowerTriangle

```
for(i=0; i<n; ++i){
    l=k-i;
    for (j=MAX(0,i-k); j<=i; ++j){
        ab[i][l+j]=A[i][j];
    }
}
```

For example, when $n = 5$ and $k = 2$:

uplo	Hermitian band matrix A	Band storage in array AB
UpperTriangle	$\begin{pmatrix} a_{11} & a_{12} & a_{13} & & \\ \bar{a}_{12} & a_{22} & a_{23} & a_{24} & \\ \bar{a}_{13} & \bar{a}_{23} & a_{33} & a_{34} & a_{35} \\ & \bar{a}_{24} & \bar{a}_{34} & a_{44} & a_{45} \\ & & \bar{a}_{35} & \bar{a}_{45} & a_{55} \end{pmatrix}$	$\begin{matrix} a_{11} & a_{12} & a_{13} \\ a_{22} & a_{23} & a_{24} \\ a_{33} & a_{34} & a_{35} \\ a_{44} & a_{45} & * \\ a_{55} & * & * \end{matrix}$
LowerTriangle	$\begin{pmatrix} a_{11} & \bar{a}_{21} & \bar{a}_{31} & & \\ a_{21} & a_{22} & \bar{a}_{32} & \bar{a}_{42} & \\ a_{31} & a_{32} & a_{33} & \bar{a}_{43} & \bar{a}_{53} \\ & a_{42} & a_{43} & a_{44} & \bar{a}_{54} \\ & & a_{53} & a_{54} & a_{55} \end{pmatrix}$	$\begin{matrix} * & * & a_{11} \\ * & a_{21} & a_{22} \\ a_{31} & a_{32} & a_{33} \\ a_{42} & a_{43} & a_{44} \\ a_{53} & a_{54} & a_{55} \end{matrix}$

Here the elements marked * in the upper left $k \times k$ triangle and the lower right $k \times k$ triangle need not be set and are not referenced by the routines.

Unit triangular matrices

Some routines in this chapter have an option to handle unit triangular matrices (that is, triangular matrices with diagonal elements = 1). This option is specified by an argument **diag**. If **diag=UnitTriangular**, the diagonal elements of the matrix need not be stored, and the corresponding array elements are not referenced by the routines. The storage scheme for the rest of the matrix (whether conventional, packed or band) remains unchanged.

Real diagonal elements of complex matrices

Complex Hermitian matrices have diagonal elements that are by definition purely real.

On input only the real parts of the diagonal elements of Hermitian matrices are referenced. The imaginary parts of the diagonals of output Hermitian matrices are set to zero.

5.1.2. Level-2 BLAS Functions Specification

In the following specifications, the argument **ap** refers to arrays containing matrices in packed storage order.

```

void dgemv (MatrixTranspose trans, Integer m, Integer n,           f06pac
            double alpha, const double a[], Integer tda,
            const double x[], Integer incx, double beta,
            double y[], Integer incy)

void zgemv (MatrixTranspose trans, Integer m, Integer n,           f06sac
            Complex alpha, const Complex a[], Integer tda,
            const Complex x[], Integer incx, Complex beta,
            Complex y[], Integer incy)

void dgbmv (MatrixTranspose trans, Integer m, Integer n,           f06pbc
            Integer kl, Integer ku, double alpha,
            const double a[], Integer tda, const double x[],
            Integer incx, double beta, double y[],
            Integer incy)

void zgbmv (MatrixTranspose trans, Integer m, Integer n,           f06sbc
            Integer kl, Integer ku, Complex alpha,
            const Complex a[], Integer tda,
            const Complex x[], Integer incx, Complex beta,
            Complex y[], Integer incy)

void dsymv (MatrixTriangle uplo, Integer n, double alpha,         f06pcc
            const double a[], Integer tda, const double x[],
            Integer incx, double beta, double y[],
            Integer incy)

void zhmv (MatrixTriangle uplo, Integer n, Complex alpha,         f06scc
            const Complex a[], Integer tda,
            const Complex x[], Integer incx, Complex beta,
            Complex y[], Integer incy)

```

void	dsbmv(MatrixTriangle uplo, Integer n, Integer k, double alpha, const double a[], Integer tda, const double x[], Integer incx, double beta, double y[], Integer incy)	f06pdc
void	zhbmv(MatrixTriangle uplo, Integer n, Integer k, Complex alpha, const Complex a[], Integer tda, const Complex x[], Integer incx, Complex beta, Complex y[], Integer incy)	f06sdc
void	dspmv(MatrixTriangle uplo, Integer n, double alpha, const double ap[], const double x[], Integer incx, double beta, double y[], Integer incy)	f06pec
void	zhpmv(MatrixTriangle uplo, Integer n, Complex alpha, const Complex ap[], const Complex x[], Integer incx, Complex beta, Complex y[], Integer incy)	f06sec
void	dtrmv(MatrixTriangle uplo, MatrixTranspose trans, MatrixUnitTriangular diag, Integer n, const double a[], Integer tda, double x[], Integer incx)	f06pfc
void	ztrmv(MatrixTriangle uplo, MatrixTranspose trans, MatrixUnitTriangular diag, Integer n, const Complex a[], Integer tda, Complex x[], Integer incx)	f06sfc
void	dtbmv(MatrixTriangle uplo, MatrixTranspose trans, MatrixUnitTriangular diag, Integer n, Integer k, const double a[], Integer tda, double x[], Integer incx)	f06pgc
void	ztbmv(MatrixTriangle uplo, MatrixTranspose trans, MatrixUnitTriangular diag, Integer n, Integer k, const Complex a[], Integer tda, Complex x[], Integer incx)	f06sgc
void	dtpmv(MatrixTriangle uplo, MatrixTranspose trans, MatrixUnitTriangular diag, Integer n, const double ap[], double x[], Integer incx)	f06phc
void	ztpmv(MatrixTriangle uplo, MatrixTranspose trans, MatrixUnitTriangular diag, Integer n, const Complex ap[], Complex x[], Integer incx)	f06shc
void	dtrsv(MatrixTriangle uplo, MatrixTranspose trans, MatrixUnitTriangular diag, Integer n, const double a[], Integer tda, double x[], Integer incx)	f06pjc
void	ztrsv(MatrixTriangle uplo, MatrixTranspose trans, MatrixUnitTriangular diag, Integer n, const Complex a[], Integer tda, Complex x[], Integer incx)	f06sjc
void	dtbsv(MatrixTriangle uplo, MatrixTranspose trans, MatrixUnitTriangular diag, Integer n, Integer k, const double a[], Integer tda, double x[], Integer incx)	f06pkc
void	ztbsv(MatrixTriangle uplo, MatrixTranspose trans, MatrixUnitTriangular diag, Integer n, Integer k, const Complex a[], Integer tda, Complex x[], Integer incx)	f06skc
void	dtpsv(MatrixTriangle uplo, MatrixTranspose trans, MatrixUnitTriangular diag, Integer n, const double ap[], double x[], Integer incx)	f06plc
void	ztpsv(MatrixTriangle uplo, MatrixTranspose trans, MatrixUnitTriangular diag, Integer n, const Complex ap[], Complex x[], Integer incx)	f06slc
void	dger(Integer m, Integer n, double alpha, const double x[], Integer incx, const double y[], Integer incy, double a[], Integer tda)	f06pmc

<code>void zgeru(Integer m, Integer n, Complex alpha, const Complex x[], Integer incx, const Complex y[], Integer incy, Complex a[], Integer tda)</code>	f06smc
<code>void zgerc(Integer m, Integer n, Complex alpha, const Complex x[], Integer incx, const Complex y[], Integer incy, Complex a[], Integer tda)</code>	f06snc
<code>void dsyr(MatrixTriangle uplo, Integer n, double alpha, const double x[], Integer incx, double a[], Integer tda)</code>	f06ppc
<code>void zher(MatrixTriangle uplo, Integer n, double alpha, const Complex x[], Integer incx, Complex a[], Integer tda)</code>	f06spc
<code>void dspr(MatrixTriangle uplo, Integer n, double alpha, const double x[], Integer incx, double ap[])</code>	f06ppc
<code>void zhpr(MatrixTriangle uplo, Integer n, double alpha, const Complex x[], Integer incx, Complex ap[])</code>	f06spc
<code>void dsyr2(MatrixTriangle uplo, Integer n, double alpha, const double x[], Integer incx, const double y[], Integer incy, double a[], Integer tda)</code>	f06prc
<code>void zher2(MatrixTriangle uplo, Integer n, Complex alpha, const Complex x[], Integer incx, const Complex y[], Integer incy, Complex a[], Integer tda)</code>	f06src
<code>void dspr2(MatrixTriangle uplo, Integer n, double alpha, const double x[], Integer incx, const double y[], Integer incy, double ap[])</code>	f06psc
<code>void zhpr2(MatrixTriangle uplo, Integer n, Complex alpha, const Complex x[], Integer incx, const Complex y[], Integer incy, Complex ap[])</code>	f06ssc

5.1.3. Level-2 BLAS Details of Matrix-vector Operations

Throughout the following sections A^H denotes the complex conjugate of A^T and $\bar{\alpha}$ denotes the complex conjugate of the scalar α .

f06pac, f06sac, f06pbc and f06sbc

perform the operation

$$\begin{aligned}
 y &\leftarrow \alpha Ax + \beta y, & \text{when } \mathbf{trans}=\mathbf{NoTranspose}, \\
 y &\leftarrow \alpha A^T x + \beta y, & \text{when } \mathbf{trans}=\mathbf{Transpose}, \\
 y &\leftarrow \alpha A^H x + \beta y, & \text{when } \mathbf{trans}=\mathbf{ConjugateTranspose},
 \end{aligned}$$

where A is a general matrix for f06pac and f06sac, and is a general band matrix for f06pbc and f06sbc.

f06pcc, f06scc, f06pec, f06sec, f06pdc and f06sdc

perform the operation

$$y \leftarrow \alpha Ax + \beta y$$

where A is symmetric and Hermitian for f06pcc and f06scc respectively, is symmetric and Hermitian stored in packed form for f06pec and f06sec respectively, and is symmetric and Hermitian band for f06pdc and f06sdc.

f06pfc, f06sfc, f06phc, f06shc, f06pgc and f06sgc

perform the operation

$$\begin{aligned}
 x &\leftarrow Ax, & \text{when } \mathbf{trans}=\mathbf{Notranspose}, \\
 x &\leftarrow A^T x, & \text{when } \mathbf{trans}=\mathbf{Transpose}, \\
 x &\leftarrow A^H x, & \text{when } \mathbf{trans}=\mathbf{ConjugateTranspose},
 \end{aligned}$$

where A is a triangular matrix for f06pfc and f06sfc, is a triangular matrix stored in packed form for f06phc and f06shc, and is a triangular band matrix for f06pgc and f06sgc.

f06pjc, f06sjc, f06plc, f06slc, f06pkc and f06skc

solve the equations

$$\begin{aligned}
 Ax &= b, & \text{when } \mathbf{trans}=\mathbf{Notranspose}, \\
 A^T x &= b, & \text{when } \mathbf{trans}=\mathbf{Transpose}, \\
 A^H x &= b, & \text{when } \mathbf{trans}=\mathbf{ConjugateTranspose},
 \end{aligned}$$

where A is a triangular matrix for f06pjc and f06sjc, is a triangular matrix stored in packed form for f06plc and f06slc, and is a triangular band matrix for f06pkc and f06skc. The vector b must be supplied in the array \mathbf{x} and is overwritten by the solution. It is important to note that no test for singularity is included in these functions.

f06pmc and f06smc

perform the operation $A \leftarrow \alpha xy^T + A$, where A is a general matrix.

f06snc

performs the operation $A \leftarrow \alpha xy^H + A$, where A is a general complex matrix.

f06ppc and f06pqc

perform the operation $A \leftarrow \alpha xx^T + A$, where A is a symmetric matrix for f06ppc and is a symmetric matrix stored in packed form for f06pqc.

f06spc and f06sqc

perform the operation $A \leftarrow \alpha xx^H + A$, where A is an Hermitian matrix for f06spc and is an Hermitian matrix stored in packed form for f06sqc.

f06prc and f06psc

perform the operation $A \leftarrow \alpha xy^T + \alpha yx^T + A$, where A is a symmetric matrix for f06prc and is a symmetric matrix stored in packed form for f06psc.

f06src and f06ssc

perform the operation $A \leftarrow \alpha xy^H + \overline{\alpha} yx^H + A$, where A is an Hermitian matrix for f06src and is an Hermitian matrix stored in packed form for f06ssc.

The following argument values are invalid:

Any value of the enumerated arguments **diag**, **trans**, or **uplo** whose meaning is not specified.

m < 0

n < 0

kl < 0

ku < 0

k < 0

tda < **n** for the functions involving general matrices or full Hermitian, symmetric or triangular matrices

tda < **kl** + **ku** + 1 for the functions involving general band matrices

tda < **k** + 1 for the functions involving band Hermitian, symmetric or triangular matrices

incx = 0

incy = 0

If a function is called with an invalid value then an error message is output on stderr, giving the name of the function and the number of the first invalid argument, and execution is terminated.

5.2. The Level-3 Matrix-matrix Functions

The matrix-matrix functions all have either two or three arguments representing a matrix, one of which is an input-output argument, and in each case the arguments are two-dimensional arrays.

The sizes of the matrices are determined by one or more of the arguments **m**, **n** and **k**. The size of the input-output array is always determined by the arguments **m** and **n** for a rectangular m by n matrix, and by the argument **n** for a square n by n matrix. It is permissible to call the functions with **m** or **n**=0, in which case the functions exit immediately without referencing their array arguments.

Many of the functions perform an operation of the form

$$C \leftarrow P + \beta C,$$

where P is the product of two matrices, or the sum of two such products. When the inner dimension of the matrix product is different from m or n it is denoted by **k**. Again it is permissible to call the functions with **k** = 0; and if **m** > 0 and **n** > 0, but **k** = 0, then the functions perform the operation

$$C \leftarrow \beta C.$$

As with the Level-2 functions (see Section 4.1) the description of the matrix consists of the array name (**a** or **b** or **c**) followed by the second dimension (**tda** or **tdb** or **tdc**).

The arguments that specify options are enumerated arguments with the names **side**, **transa**, **transb**, **trans**, **uplo** and **diag**. **uplo** and **diag** have the same values and meanings as for the Level-2 functions (see Section 4.1); **transa**, **transb** and **trans** have the same values and meanings as **trans** in the Level-2 functions, where **transa** and **transb** apply to the matrices A and B respectively. **side** is used by the functions as follows:

Value	Meaning
LeftSide	Multiply general matrix by symmetric, Hermitian or triangular matrix on the left
Rightside	Multiply general matrix by symmetric, Hermitian or triangular matrix on the right

The storage conventions for matrices are as for the Level-2 functions (see Section 4.1).

5.2.1. Level-3 BLAS Functions Specification

```

void dgemm(MatrixTranspose transa, MatrixTranspose transb,      f06yac
           Integer m, Integer n, Integer k, double alpha,
           const double a[], Integer tda, const double b[],
           Integer tdb, double beta, double c[], Integer tdc)

void zgemm(MatrixTranspose transa, MatrixTranspose transb,      f06zac
           Integer m, Integer n, Integer k, Complex alpha,
           const Complex a[], Integer tda, const Complex b[],
           Integer tdb, Complex beta, Complex c[],
           Integer tdc)

void dsymm(OperationSide side, MatrixTriangle uplo,           f06ycc
           Integer m, Integer n, double alpha,
           const double a[], Integer tda, const double b[],
           Integer tdb, double beta, double c[], Integer tdc)

void zhemm(OperationSide side, MatrixTriangle uplo,           f06zcc
           Integer m, Integer n, Complex alpha,
           const Complex a[], Integer tda, const Complex b[],
           Integer tdb, Complex beta, Complex c[],
           Integer tdc)

```

void dtrmm(MatrixTriangle side, MatrixTriangle uplo, MatrixTranspose transa, MatrixUnitTriangular diag, Integer m, Integer n, double alpha, const double a[], Integer tda, double b[], Integer tdb)	f06yfc
void ztrmm(MatrixTriangle side, MatrixTriangle uplo, MatrixTranspose transa, MatrixUnitTriangular diag, Integer m, Integer n, Complex alpha, const Complex a[], Integer tda, Complex b[], Integer tdb)	f06zfc
void dtrsm(OperationSide side, MatrixTriangle uplo, MatrixTranspose transa, MatrixUnitTriangular diag, Integer m, Integer n, double alpha, const double a[], Integer tda, double b[], Integer tdb)	f06yjc
void ztrsm(OperationSide side, MatrixTriangle uplo, MatrixTranspose transa, MatrixUnitTriangular diag, Integer m, Integer n, Complex alpha, const Complex a[], Integer tda, Complex b[], Integer tdb)	f06zjc
void dsyrk(MatrixTriangle uplo, MatrixTranspose trans, Integer n, Integer k, double alpha, const double a[], Integer tda, double beta, double c[], Integer tdc)	f06ypc
void zherk(MatrixTriangle uplo, MatrixTranspose trans, Integer n, Integer k, double alpha, const Complex a[], Integer tda, double beta, Complex c[], Integer tdc)	f06zpc
void dsyr2k(MatrixTriangle uplo, MatrixTranspose trans, Integer n, Integer k, double alpha, const double a[], Integer tda, const double b[], Integer tdb, double beta, double c[], Integer tdc)	f06yrc
void zher2k(MatrixTriangle uplo, MatrixTranspose trans, Integer n, Integer k, Complex alpha, const Complex a[], Integer tda, const Complex b[], Integer tdb, double beta, Complex c[], Integer tdc)	f06zrc
void zsymm(OperationSide side, MatrixTriangle uplo, Integer m, Integer n, Complex alpha, const Complex a[], Integer tda, const Complex b[], Integer tdb, Complex beta, Complex c[], Integer tdc)	f06ztc
void zsyrk(MatrixTriangle uplo, MatrixTranspose trans, Integer n, Integer k, Complex alpha, const Complex a[], Integer tda, Complex beta, Complex c[], Integer tdc)	f06zuc
void zsyr2k(MatrixTriangle uplo, MatrixTranspose trans, Integer n, Integer k, Complex alpha, const Complex a[], Integer tda, const Complex b[], Integer tdb, Complex beta, Complex c[], Integer tdc)	f06zwc

5.2.2. Level-3 BLAS Matrix-matrix Details of Operations

Here as in Section 4.1.2, A^H denotes the complex conjugate of A^T and $\bar{\alpha}$ denotes the complex conjugate of the scalar α .

f06yac and **f06zac**

perform the operation indicated in the following table:

	transa=Notranspose	transa=Transpose	transa=ConjugateTranspose
transb=Notranspose	$C \leftarrow \alpha AB + \beta C$ A is $m \times k$, B is $k \times n$	$C \leftarrow \alpha A^T B + \beta C$ A is $k \times m$, B is $k \times n$	$C \leftarrow \alpha A^H B + \beta C$ A is $k \times m$, B is $k \times n$
transb=Transpose	$C \leftarrow \alpha AB^T + \beta C$ A is $m \times k$, B is $n \times k$	$C \leftarrow \alpha A^T B^T + \beta C$ A is $k \times m$, B is $n \times k$	$C \leftarrow \alpha A^H B^T + \beta C$ A is $k \times m$, B is $n \times k$
transb=ConjugateTranspose	$C \leftarrow \alpha AB^H + \beta C$ A is $m \times k$, B is $n \times k$	$C \leftarrow \alpha A^T B^H + \beta C$ A is $k \times m$, B is $n \times k$	$C \leftarrow \alpha A^H B^H + \beta C$ A is $k \times m$, B is $n \times k$

where A and B are general matrices and C is a general m by n matrix.

f06ycc, **f06zcc** and **f06ztc** perform the operation indicated in the following table:

side=Leftside	side=Rightside
$C \leftarrow \alpha AB + \beta C$	$C \leftarrow \alpha BA + \beta C$
A is $m \times m$	B is $m \times n$
B is $m \times n$	A is $n \times n$

where A is symmetric for **f06ycc** and **f06ztc** and is Hermitian for **f06zcc**, B is a general matrix and C is a general m by n matrix.

f06yfc and **f06zfc** perform the operation indicated in the following table:

	transa=Notranspose	transa=Transpose	transa=ConjugateTranspose
side=Leftside	$B \leftarrow \alpha AB$ A is triangular $m \times m$	$B \leftarrow \alpha A^T B$ A is triangular $m \times m$	$B \leftarrow \alpha A^H B$ A is triangular $m \times m$
side=Rightside	$B \leftarrow \alpha BA$ A is triangular $n \times n$	$B \leftarrow \alpha BA^T$ A is triangular $n \times n$	$B \leftarrow \alpha BA^H$ A is triangular $n \times n$

where B is a general m by n matrix.

f06yjc and **f06zjc** solve the equations, indicated in the following table, for X :

	transa=Notranspose	transa=Transpose	transa=ConjugateTranspose
side=Leftside	$AX = \alpha B$ A is triangular $m \times m$	$A^T X = \alpha B$ A is triangular $m \times m$	$A^H X = \alpha B$ A is triangular $m \times m$
side=Rightside	$XA = \alpha B$ A is triangular $n \times n$	$XA^T = \alpha B$ A is triangular $n \times n$	$XA^H = \alpha B$ A is triangular $n \times n$

where B is a general m by n matrix. The m by n solution matrix X is overwritten on the array B . It is important to note that no test for singularity is included in these functions.

f06ypc, **f06zpc** and **f06zuc** perform the operation indicated in the following table:

	trans=Notranspose	trans=Transpose	trans=ConjugateTranspose
f06ypc	$C \leftarrow \alpha AA^T + \beta C$	$C \leftarrow \alpha A^T A + \beta C$	$C \leftarrow \alpha A^T A + \beta C$
f06zuc	$C \leftarrow \alpha AA^T + \beta C$	$C \leftarrow \alpha A^T A + \beta C$	—
f06zpc	$C \leftarrow \alpha AA^H + \beta C$ A is $n \times k$	— A is $k \times n$	$C \leftarrow \alpha A^H A + \beta C$ A is $k \times n$

where A is a general matrix and C is an n by n symmetric matrix for f06ypc and f06zuc, and is an n by n Hermitian matrix for f06zpc.

f06yrc, **f06zrc** and **f06zwc** perform the operation indicated in the following table:

	trans=Notranspose	trans=Transpose	trans=ConjugateTranspose
f06yrc	$C \leftarrow \alpha AB^T + \alpha BA^T + \beta C$	$C \leftarrow \alpha A^T B + \alpha B^T A + \beta C$	$C \leftarrow \alpha A^T B + \alpha B^T A + \beta C$
f06zwc	$C \leftarrow \alpha AB^T + \alpha BA^T + \beta C$	$C \leftarrow \alpha A^T B + \alpha B^T A + \beta C$	—
f06zrc	$C \leftarrow \alpha AB^H + \overline{\alpha} BA^H + \beta C$	—	$C \leftarrow \alpha A^H B + \overline{\alpha} B^H A + \beta C$
	A and B are $n \times k$	A and B are $k \times n$	A and B are $k \times n$

where A and B are general matrices and C is an n by n symmetric matrix for f06yrc and f06zwc, and is an n by n Hermitian matrix for f06zpc.

The following values of arguments are invalid:

Any value of the enumerated arguments **side**, **transa**, **transb**, **trans**, **uplo** or **diag**, whose meaning is not specified.

m < 0

n < 0

k < 0

tda < the number of columns in the matrix A .

tdb < the number of columns in the matrix B .

tdc < the number of columns in the matrix C .

If a function is called with an invalid value, then an error message is output on stderr, giving the name of the function and the number of the first invalid argument, and execution is terminated.